



## APE Model 100 Vibratory Driver Extractor

The Worlds Largest Provider of  
Foundation Construction Equipment



SPECIFICATIONS	DATA
Eccentric Moment	2,200 in-lbs (25.35 kgm)
Drive Force	85 tons (757 kN)
Frequency Maximum (VPM)	0 - 1,650 vpm
Max Line Pull	45 tons (400 kN)
Bare Hammer Weight w/o Clamp	5,900 lbs (2,676 kg)
Throat Width	14.50 in (37 cm)
Length	61.88 in (157 cm)
Height w/o Clamp	54.13 in (137 cm)

## APE Model 275 Power Unit

SPECIFICATIONS	DATA
Engine Type	Caterpillar C7 Tier III
Horse Power	275 HP (202 kW)
Drive Pressure	0 - 4,800 psi (331 bar)
Drive Flow	74 gpm (280 lpm)
Clamp Pressure	4,800 psi (69,618 bar)
Clamp Flow	10 gpm (3 lpm)
Engine Speed	2,100 rpm
Weight	11,500 lbs (5,216 kg)
Length	117 in (296 cm)
Width	59 in (149 cm)
Height	84 in (212 cm)
Hydraulic Reservoir	225 gal (852 L)
Fuel Capacity	80 gal (303 L)



Specifications may vary due to site conditions, specific hammer conditions or product set up.  
Specifications may change without notice.  
Consult the factory for details on any specific product (800) 248-8498.

**WWW.APEVIBRO.COM**  
(800) 248-8498  
webmaster@apevibro.com

